

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (Currently Amended): A bottle can member which is made of [[a]] metal ~~member~~ in a cylindrical shape with a bottom section comprising:

a thread section on a mouth section comprising:

an outer diameter of the thread section which is formed on the mouth section is 28 to 38 mm;

a thickness of the thread section is 0.25 to 0.4 mm; ~~and~~

an effective thread number of the thread section is 2.0 to 2.5 ; and

a height “h” from a starting point of the thread in the thread section to an upper end surface of the mouth section is set to be in a range of $0.7 \leq (D1-D2)/h \leq 1.3$ under the condition that D1 indicates an outer diameter of the thread and D2 indicates an outer diameter of a curl section.

Claim 2 (Previously Presented): A bottle can member according to Claim 1 wherein

the thread section further comprises:

a thread pitch of the thread section formed on the mouth section is 8 threads per an inch.

Claim 3. (Cancelled)

Claim 4 (Currently Amended): A bottle can member according to Claim 1 further comprising:

~~an~~ a slant angle θ of a slant section is set to be in a range of 33° ~~[[$\leq\theta\leq$]]~~ $\leq\theta\leq 55^{\circ}$.

Claim 5 (Currently Amended): A bottle wherein a cap is put on ~~[[a]]~~ the mouth section of the bottle can member according to Claim 1.

Claim 6 (Previously Presented): A bottle can member according to Claim 1 further comprising

a height of a first thread in a thread area in the thread section is set to be lower than a height of another thread in a predetermined angle range.

Claim 7 (Currently Amended): A bottle can member according to Claim 1 wherein
in an area except an area which overlaps a plurality of stages and an incomplete thread section in a thread end section, a height of the thread in the first thread is set to be lower than
a ~~the~~ height of the second thread.

Claim 8 (Currently Amended): A bottle comprising the bottle can member according to Claim 6 and a ~~the~~ cap which is put on the mouth section of the bottle can member.

Claim 9 (Currently Amended): A bottle comprising the bottle can member according to Claim 7 and ~~a~~ the cap which is put on the mouth section of the bottle can member.

Claim 10 (Withdrawn): A method for forming a mouth section on the bottle can member comprising the step of forming a thread section which has a thread area which is formed by a plurality of stages toward a can bottom direction from a tip of the mouth section around an outer periphery of the mouth section of the bottle can member wherein:


a thread number is 2.0 to 2.5; and

when a thread section is formed, a height of the first thread which is disposed near a tip of the mouth section of the bottle can member is set to be lower than the thread of other stages in a predetermined angle range.

Claim 11 (Withdrawn): A method for forming a mouth section of the bottle can member according to Claim 10 wherein

the predetermined angle range is in a range with in 90 degrees from the thread starting section of the thread section.

Claim 12 (Withdrawn): A thread forming device for a bottle can member comprising:
a core which contacts an inner surface of a mouth section of the bottle can member and has a thread forming section for disposing a thread section which is supposed to be formed in the mouth section on an outer periphery; and

{W:\09852\0201547-us0\01503663.DOC  }

an outer member which contacts the outer periphery of the mouth section and has a thread forming section which has a corresponding shape to the thread forming section of the core around the outer periphery, wherein,

the core and the outer member rotate around an axial center of the bottle can member while sandwiching the mouth section;

a thread section which has a thread area is formed so as to have a thread number 2.0 to 2.5;

in the thread forming section of the core, the first thread forming section for forming the first thread in the thread are in the mouth section is formed so as to be lower than the thread forming section in other stages in a predetermined angle range.